



# Chamak Paintchem Limited

1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350.  
(Gujarat) INDIA. ■ Ph. : 079-22703603, 22704607 ■ FAX : 079-22704815  
Email : info@chamakpaint.com ■ URL : www.chamakpaint.com



## CHAMAK ULTIMATE EXTERIOR EMULSION

Combines exceptional elegance with durability to keep exteriors looking ever new. As a water-based high-build 100% acrylic emulsion, it has unmatched anti-fungal, anti-flaking and anti-fading properties. Hair-line cracks are easily bridged because of its superior adhesion and plasticity. Growth of fungi and algae is curbed, and the blackening they cause in other exterior finishes prevented, by its broad spectrum biocides and fungicides. Besides, its unique one-way barrier - a special osmotic quality of the paint film - allows it to breath out moisture without absorbing any - thus protecting the brickwork and concrete.

Finish	: Smooth and Matt.
Colour	: As per shade card.
Drying Time	: Dry for a minimum of 4 hours between coats.
Flash Point	: N.A.
Thinner Recommended	: Water
Method of Application	: Brush or roller
Undercoats	: Normally no primer is required. On highly absorbent or chalky surface, apply a coat of Chamak Exterior primer Smooth thinned with water (1 : 1 by volume) as a self priming coat to reduce surface porosity.
Shelf Life	: 12 Months
Uses	: Cement, sand surfaces, brickwork, rough cast concrete blocks, fibre boards and cement paint coated surfaces.
Covering Capacity	: 12 to 13 sq. metres per litre per coat depending on the surface and shade.
Application Areas	: Cementous, asbestos & brickwork etc.
Directions of Use	: Mix one litre of Chamex Ultimate to 400 ml of water approximately before application.
Packing	: 1 ltr, 4 ltr, 10 ltr, 20 ltr.