



# Chamak Paintchem Limited

1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350.  
(Gujarat) INDIA. ■ Ph. : 079-22703603, 22704607 ■ FAX : 079-22704815  
Email : info@chamakpaint.com ■ URL : www.chamakpaint.com



## QUICK-SET RED OXIE PRIMER

CHAMAK Quick Set Red Oxide primer based on special synthetic resin & anticorrosive pigments is ideally suitable where fast drying is required. The film dries hard quickly forming a good touch coat. Notable special feature of this prime is that one can use either enamel system or N. C. system for subsequent coats.

- Recommended Use** : Applicable for ferrous substrate on . Cars, scooters, transport vehicles etc. For new fabrication work and maintenance work where quick drying is essential.
- Finish** : Smooth & matt
- Colour** : Light brown
- Covering Capacity** : For Smooth M.S. surface : approx 14 sq. m / lit per coat @ 20 micron DFT, depending on surface and spaying loss
- Drying Time** : Surface Dry - approx 15 minuts  
Hard Dry - approx 6 hours.
- Flash Point** : Above 25<sup>0</sup>
- Application Viscosity** : Brushing-50 to 60 sec @ 30<sup>0</sup> c. by FC4  
Spraying-30 to 35 sec 30<sup>0</sup> c. by FC4
- Application Method** : By Brush or Spray @ 45 P.S.I
- Subsequent Coat** : Chamak enamels N.C.P.S. Grey, N.C. putty etc
- Direction For Use** : Remove dust, oil, greas, etc, from the surface to be coated. Prior degreasing & derusting can also be done. Apply CHAMAK Quick set R/O primer by brush or spray, use recommended thinner for desire viscosity. Allow primer coat to hard dry. Sand the primer coat with sand paper and apply subsequent coats.
- Packing** : 20 lit , 4 lit , 1 lit, 500 mls.