



Chamak Paintchem Limited

1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350.
(Gujarat) INDIA. ■ Ph. : 079-22703603, 22704607 ■ FAX : 079-22704815
Email : info@chamakpaint.com ■ URL : www.chamakpaint.com



REDOXIDE METAL PRIMER

CHAMAK Red Oxid metal primer is most economical primer. It has good adhesion & gives fairly good corrosion to metal. It can be brushed or sprayed. It gives good & tough coating on metal surface

Recommended Use	: It is applied on steel furnitures industry,
Finish	: Smooth & matt
Colour	: Light brown
Covering Capacity	: For Smooth M.S. surface : approx 14 sq. m / lit per coat @ 20 micron DFT, depending on surface and spaying loss
Drying Time	: Surface Dry - approx 15 minuts Hard Dry - approx 6 hours.
Flash Point	: Above 25 ⁰
Application Viscosity	: Brushing-50 to 60 sec @ 30 ⁰ c. by FC4 Spraying-30 to 35 sec 30 ⁰ c. by FC4
Application Method	: By Brush or Spray @ 45 P.S.I
Subsequent Coat	: Chamak enamels N.C.P.S. Grey, N.C. putty etc
Direction For Use	: Remove dust, oil, grease etc, from the surface to be coated. Prior degreasing & derusting can also be done. Apply CHAMAK Quick set R/O primer by brush or spray, use recommended thinner for desire viscosity. Allow primer coat to hard dry. Sand the primer coat with sand paper and apply subsequent coats.
Packing	: 20 lit , 4 lit , 1 lit, 500 mls.