



Chamak Paintchem Limited

1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350.
(Gujarat) INDIA. ■ Ph. : 079-22703603, 22704607 ■ FAX : 079-22704815
Email : info@chamakpaint.com ■ URL : www.chamakpaint.com



CHAMAK PREMIUM EMULSION

Chamak Premium Emulsion is an acrylic pearlescent glaze ideal for creating shimmering wall finishes and softly sparkled features to add visual interest and diversity to any colour scheme. Chamak Premium Emulsion is always used in conjunction with a basecoat tinted to a selected colour. The Choice of basecoat will depend on whether it is an interior or exterior application. Chamak Premium Emulsion may be applied over a wide variety of substrates, including trim and joinery, offering the user an almost infinite selection of colours.

Finish	: Smooth & Glossy
Colour	: As per the Shade card.
Drying Time	: 45 minutes at 18°C
Flash Point	: N.A
Thinner Recommended	: Water; in hot dry conditions may be thinned with up to 5% Resene Hot Weather Additive
Method of Application	: Brush or roller.,
Undercoats	: Chamak Cement primer ST/WT
Shelf Life	: 3 Years from the date of manufacture in original tightly closed container. Stay away from direct sunlight and excessive heat. Stability of Thinned Paint : Use within 24 hrs.
Uses	: Architraves, Bathrooms, Cementitious surfaces, Furniture, Kitchens, Laundries, Paperfaced plasterboard, Plywood, Skirtings, Timber doors, Wallboards, Window Frames
Covering Capacity	: 10-40 sq. metres per litre dependent on surface and technique
Application Areas	: Cementous, asbestos & brickwork etc.
Packing	: 1ltr, 4ltr, 10ltr, 20ltr.